

Serial No. 10/805,634
Reply to Office Action of August 19, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (original) A method of adjusting a group delay adjusting circuit comprising:
 - applying a capacitive control signal to adjust a first variable capacitance;
 - adjusting the first variable capacitance by applying the capacitive control signal to the first variable capacitance such that the capacitance of the group delay adjusting circuit is adjusted;
 - applying an inductive control signal to a second variable capacitance; and
 - adjusting the second variable capacitance by applying the inductive control signal to the second variable capacitance of a virtual inductor such that the inductance of the group delay adjusting circuit is adjusted.
2. (original) The method of claim 1, further comprising the step of applying a signal to the group delay adjusting circuit prior to the step of applying a capacitive control signal.
3. (original) The method of claim 2, further comprising the step of measuring a group delay of the signal prior to the step of adjusting the first variable capacitance.
4. (original) A method of adjusting a group delay adjusting circuit comprising:
 - applying a capacitate control signal to adjust a first variable capacitance;
 - adjusting the first variable capacitance by applying conjunctional positive capacitive control signal to the first variable capacitance;

Serial No. 10/805,634

Reply to Office Action of August 19, 2005

applying an inductive control signal to a second variable capacitance; and
adjusting the second variable capacitance by applying a conjunctional
positive inductive control signal to the second variable capacitance.

5. (original) The method of claim 4, further comprising the step of
applying a signal to the group delay adjusting circuit prior to the step of applying a
capacitive control signal.

6. (original) The method of claim 5, further comprising the step of
measuring a group delay of the signal prior to the step of adjusting the first variable
capacitance.

7. (original) A group delay adjusting circuit, comprising:
a transmission line having an input and an output; and
a stub matching structure including a virtual inductor having a first terminal
coupled to the transmission line and a second terminal coupled to ground, and
including a first delay adjust signal input, a second delay adjust signal input and a
DC bias input;

whereby a group delay of a signal envelope coupled to the input of the
transmission line is adjusted at the output of the transmission line, by coupling a
first variable voltage to the first delay adjust signal input, coupling a second variable
voltage to the second delay adjust signal input, and coupling a DC bias voltage to
the DC bias input.

8. (original) The group delay adjusting circuit of claim 7, wherein the
transmission line is a microstrip transmission line.

9. (original) The group delay adjusting circuit of claim 7, wherein the
transmission line is a stripline transmission line.

Serial No. 10/805,634

Reply to Office Action of August 19, 2005

10. (original) The group delay adjusting circuit of claim 7, wherein the transmission line length is arbitrary.

11. (original) The group delay adjusting circuit of claim 10, wherein the virtual inductor includes a quarter wave transmission line having a first terminal coupled to the transmission line and a second terminal coupled to a first terminal of a variable capacitor, and having a second terminal of the variable capacitor coupled to ground.

12. (original) The group delay adjusting circuit of claim 7, wherein the first delay adjust signal input and the second delay adjust signal are responsive to varying voltages.

13. (currently amended) A group delay adjusting circuit comprising:
an electronically adjustable variable capacitance having its capacitance adjusted by a first delay adjust signal; [[and]]

an electronically variable virtual inductor having its inductance adjusted by a second delay adjust signal, coupled in parallel to the electronically variable capacitance at a node; and

a transmission line coupled to the electronically variable virtual inductor and the electronically adjustable variable capacitor at the node,

whereby a signal envelope having a group delay applied to the node is adjusted by the capacitance and inductance such that the group delay is adjusted.

14. (original) The group delay adjusting circuit of claim 13, wherein the electronically variable capacitance comprises a first terminal coupled to a first terminal of the electronically variable virtual inductor, and a second terminal coupled to ground.

Serial No. 10/805,634

Reply to Office Action of August 19, 2005

15. (original) The group delay adjusting circuit of claim 13, wherein the electronically variable virtual inductor comprises a first terminal coupled to a first terminal of the electronically variable capacitor, and a second terminal coupled to ground.

16. (canceled)

17. (original) The group delay adjusting circuit of claim 13, further comprising a capacitive control input coupled to a first delay adjust voltage signal.

18. (original) The group delay adjusting circuit of claim 13, further comprising an inductive control input coupled to a second delay adjust voltage signal.

19. (original) A group delay adjusting circuit comprising:
a means for providing an electronically adjustable variable capacitance; and
a means for providing an electronically variable inductance coupled in parallel to the means for providing an electronically adjustable capacitance;
whereby the parallel combination includes a first signal node coupled to a signal, and a second ground node coupled to a ground potential;
whereby a signal envelope having a group delay applied to the node is adjusted by the electronically adjustable variable capacitance and the electronically adjustable variable inductance such that the group delay is adjusted.

20. (original) A method of providing group delay adjustment comprising:
adjusting a first parallel variable shunt capacitance having a first terminal and a second terminal coupled to a ground;
adjusting a second variable shunt capacitance; and
electrically rotating the second variable shunt capacitance to a variable inductance by coupling the variable shunt capacitance to a first terminal of a series

Serial No. 10/805,634

Reply to Office Action of August 19, 2005

transmission line having an electrical length of a quarter wavelength at a frequency of operation, in which a second terminal of the series transmission line is coupled to the first terminal of the first parallel variable shunt capacitance such that the second terminal of the series transmission line provides a variable inductance;

whereby the second variable shunt capacitance is transformed into a variable inductance by the series transmission line and group delay is adjusted.

21. (original) A method of providing group delay adjustment comprising:
setting a first control voltage to a first value;
adjusting a second control voltage to produce a predetermined insertion loss flatness;
measure a phase at a low frequency;
measure the phase at a high frequency;
calculate the group delay; and
record the first control voltage, the second control voltage values and group delay.

22. (original) The method of providing group delay adjustment of claim 21, further comprising:
incrementing the first control voltage from the first value in a plurality of differential steps until a final control voltage is achieved;
each step of the plurality of differential steps includes the steps of adjusting the second control voltage value until a best insertion loss flatness is achieved while the first control voltage is fixed;
measure a phase at a lowest frequency;
measure the phase at a highest frequency;
calculate a group delay; and
record the first control voltage value, the second control voltage value and the group delay.

Serial No. 10/805,634
Reply to Office Action of August 19, 2005

23. (original) A method of providing group delay adjustment of claim 22 further comprising:

calculating an inverse first control voltage and an inverse second control voltage functions based on a first and a second control voltage and group delay accumulated data, to provide a first and a second control voltage for a given desired group delay within range of group delay adjustment range;

storing the group delay to produce the first and the second control voltage functions in a digital to analog converter; and

providing digital to analog conversion wherein group delay to first and second control voltage functions provides on demand command conversion from a digital word to a first and a second control voltage setting to provide a desired group delay setting.

24. (original) A method of providing group delay adjustment of claim 23 further comprising providing digital to analog conversion wherein group delay to first and second control voltage functions includes temperature compensation to maintain a desired group delay setting over a full operating temperature range.